International Journal of
Supply Chain and Logistics
(IJSCL)

Synchronous Goods Movement Posting in Embedded SAP EWM on SAP S/4HANA



CARI Journals

International Journal of Supply Chain and Logistics

ISSN 2520-3983 (Online)

Vol. 10, Issue No. 7, pp 36 - 46, 2026

www.carijournals.org

Synchronous Goods Movement Posting in Embedded SAP EWM on SAP S/4HANA

Vinaykumar Sharma[1]*, Rajashiva Ramalingam[2]

[1]MYGO Consulting Inc., SAP EWM Lead Consultant

https://orcid.org/0009-0005-7220-0938

[2]ACCO Brands, Manager, SAP Transportation Management

Accepted: 4th Oct, 2026, Received in Revised Form: 20th Oct, 2026, Published: 3rd Nov, 2026

ABSTRACT

Purpose: This study evaluates synchronous goods movement posting in embedded SAP Extended Warehouse Management (EWM) as an alternative to delivery-based integration for eligible goods receipt and goods issue scenarios. It asks which functional and architectural conditions justify synchronous posting and where delivery-based processing remains necessary.

Methodology: A structured comparative technical review was conducted using SAP product documentation and release information, SAP Community and practitioner sources, and established enterprise-integration literature. Sources were selected when they described at least one of four topics: release scope, process flow, configuration prerequisites, or functional exclusions. Claims were compared across sources and organized into deployment, functional-scope, document-flow, error-handling, and coupling dimensions. Three constructed scenarios were then used to demonstrate the decision framework. A sensitivity analysis illustrates potential labor effects; it is explicitly an assumption-based planning model rather than an observed business result.

Findings: For supported movements in embedded EWM synchronous posting can avoid the intermediate Delivery and Warehouse Request documents, eliminate the delivery-distribution queue for the movement in question, update both Inventory Management and EWM in a single logical unit of work and return errors at posting time. It won't work in any scenario where you need functionality that is outside of the supported scope (i.e. selected quality, packing, serialization, handling unit or decentralised EWM). The primary architectural trade-off is reduced document and queue overhead against tighter runtime coupling and a much more constrained functional scope.

Unique Contribution to Theory, Practice and Policy: The article contributes a two-stage selection framework: mandatory eligibility gates followed by weighted shaping criteria. It also converts an unsupported single-point value claim into a transparent sensitivity model and provides implementation controls, pilot measures, and rollback criteria.

Keywords: *SAP Extended Warehouse Management, Embedded EWM, Synchronous Goods Movement, SAP S/4HANA, Goods Receipt, Integration Architecture*

JEL Codes: *L86, M15, O33*

International Journal of Supply Chain and Logistics
ISSN 2520-3983 (Online)
Vol. 10, Issue No. 7, pp 36 - 46, 2026
www.carijournals.org

1. INTRODUCTION

SAP S/4HANA warehouses commonly use delivery-based integration to connect Inventory Management (IM) postings with EWM execution. This model provides broad functional coverage, but even a straightforward goods receipt may involve a material document, an inbound delivery, an EWM warehouse request, and warehouse tasks. The distribution step is asynchronous and can therefore require queue monitoring and later error resolution [1], [2].

Synchronous goods movement posting provides an alternative for supported scenarios in embedded EWM. SAP documentation for SAP S/4HANA 2020 identifies synchronous goods movement with the Post Goods Movement app, while practitioner documentation places purchase-order-based external procurement support in SAP S/4HANA 2020 FPS01 [3], [4]. In eligible cases, IM and EWM are posted together without creating the inbound delivery and warehouse request that characterize the delivery-based flow [4].

The practical problem is not whether synchronous posting exists, but how to select it without overstating its scope or benefits. A simpler document chain may reduce operational friction, yet synchronous processing also increases runtime dependence between participating components and does not reproduce every delivery-based capability. No claim is made here that simple movements dominate every warehouse. The relevant movement share must be measured at each site.

This study has three objectives: (1) compare delivery-based and synchronous integration on a consistent set of architectural and operational dimensions; (2) identify mandatory eligibility constraints and weighted selection criteria; and (3) provide a transparent, testable method for estimating value through a controlled pilot. The research question is: Under what conditions should an embedded-EWM design use synchronous posting rather than the delivery-based flow?

2. LITERATURE REVIEW

SAP product documentation defines the supported architecture and release-dependent capabilities of embedded EWM [1]-[3]. SAP Community sources provide practical explanations of purchase-order-based synchronous goods receipt, destination-bin selection, online error handling, and the absence of delivery-distribution queues for covered postings [4]. Practitioner material also documents production integration, including synchronous goods receipt and backflush consumption [5], [6]. These sources are strongest on configuration and execution but provide limited guidance for comparing candidate processes at design time.

The architectural lens used in this study comes from enterprise integration patterns. Hohpe and Woolf distinguish synchronous request-response interaction from asynchronous messaging and explain the resulting trade-offs in temporal coupling, failure handling, and throughput management [7]. Applied to embedded EWM, synchronous posting removes the asynchronous delivery handoff for the covered movement, but a posting can complete only when the participating logic is

available and valid. This makes availability, peak-load behavior, and failure propagation relevant design considerations rather than secondary technical details.

The gap is therefore a selection problem. SAP sources explain what the function does, and practitioner sources show how it can be configured, but they do not provide a transparent method that separates non-negotiable eligibility constraints from contextual business preferences. The framework below addresses that gap.

3. METHODOLOGY

This article uses a structured comparative technical review rather than an empirical field experiment. Searches were limited to sources that directly addressed synchronous goods movement in embedded EWM or a clearly relevant integration concept. Priority was given to SAP Help and SAP support content for product scope, followed by named practitioner sources for configuration and observed system behavior. General marketing statements and unverified performance percentages were excluded.

Each retained source was coded against five comparison dimensions: deployment model, supported process/function, document flow, error-handling point, and coupling characteristic. Statements were cross-checked where possible. Release-specific claims are stated only where the cited source identifies a release. The resulting framework was derived in two steps. First, conditions that make synchronous posting unavailable or inappropriate were classified as gates. Second, remaining contextual criteria were classified as shaping factors and assigned weights for a pilot decision.

The three application scenarios are constructed examples based on documented capabilities; they are not presented as observed customer case studies. They were chosen to represent a clearly eligible flow, a clearly ineligible flow, and a mixed portfolio. The financial illustration is also constructed. Its parameters are visible and varied in a sensitivity table so readers can replace them with site data.

4. COMPARISON OF THE TWO INTEGRATION MODELS

Figure 1 compares the logical document paths. The figure is a conceptual representation derived from SAP documentation and does not imply that every delivery-based process has the same number of warehouse tasks.

International Journal of Supply Chain and Logistics
ISSN 2520-3983 (Online)
Vol. 10, Issue No. 7, pp 36 - 46, 2026
www.carijournals.org




Figure 1. Conceptual comparison of delivery-based and synchronous goods movement in embedded EWM.

In delivery-based integration, the delivery and warehouse request provide process objects, statuses, and functional hooks used by complex execution. In synchronous posting, the covered movement is processed without those intermediate objects [4]. This is a functional simplification, not merely a screen change. The design benefit is strongest where those process objects are not needed; the design risk increases where they carry essential warehouse controls.

Table 1. Architectural comparison. Statements are qualitative; no performance ranking is implied

Dimension	Delivery-based flow	Synchronous flow
Communication	Asynchronous delivery distribution and follow-on EWM processing	Synchronous processing within the posting transaction for supported movements
Intermediate objects	Delivery and EWM warehouse request are available	No delivery or warehouse request for the covered posting
Deployment	Applicable to broader embedded and decentralized designs	Embedded EWM only, according to the cited PO-based guidance [4]
Error point	Errors may appear during distribution or follow-on processing	Validation errors are returned during posting [4]
Functional breadth	Preferred where delivery functions are required	Use only within release- and scenario-specific supported scope

Dimension	Delivery-based flow	Synchronous flow
Runtime dependency	Messaging can buffer temporary differences in availability	Posting depends on synchronous validation and execution availability

5. TECHNICAL MECHANISM AND CONFIGURATION BOUNDARY

For an eligible posting, the user initiates the goods movement in MIGO or the relevant app. The synchronous EWM integration validates warehouse-relevant data and posts the IM and EWM effects together. A destination bin may be selected through the Warehouse Management area, and a putaway warehouse task can be created when the relevant settings permit it [3], [4]. This article does not assert specific internal function-module or class names because those implementation details were not independently system-tested by the authors for a declared release.




Figure 2. Logical mechanism used for analysis; internal class names are intentionally excluded.

For production integration, cited practitioner guidance describes synchronous goods receipt and consumption, with activation and warehouse-process-type settings under EWM goods-movement Customizing [6]. Exact paths and field behavior should be verified in the target SAP S/4HANA release because configuration labels and supported movements can change. KBA 3452904 is a relevant SAP support reference for activation, but access-controlled support content should be checked by the implementation team before design sign-off [8].

The functional boundary must be confirmed against the target release. Purchase-order-based guidance states that the function is for embedded EWM and is not available in decentralized EWM [4]. Processes requiring quality inspection, value-added services, or delivery-centric packing controls should not be assumed eligible merely because a goods movement type exists. The safe design rule is to treat support as scenario-specific and verify required functions one by one.

Table 2. Evidence-based screening criteria

Requirement	Decision treatment	Evidence required before approval
Embedded EWM deployment	Mandatory gate	Target system architecture and warehouse assignment
Release supports the exact movement/scenario	Mandatory gate	Current SAP Help, release note, or SAP support document
No indispensable delivery-based function	Mandatory gate	Process design covering QM, HU, serialization, packing, returns, output, and compliance
Destination/source bin can be determined	Shaping criterion	Master-data test and exception-rate sample
Process is operationally simple	Shaping criterion	Documented steps and exception paths
Queue/latency burden is material	Shaping criterion	Baseline queue incidents, age, and support effort
Synchronous availability risk is acceptable	Shaping criterion	Peak-load and negative-path test results

6. DECISION FRAMEWORK

The framework first applies gates. Any failed gate leads to delivery-based processing. Eligible candidates are then scored on four shaping criteria using a 1-5 scale, where 5 favors synchronous posting: process simplicity (30%), deterministic bin/master data (25%), measurable queue or latency burden (25%), and fit with the existing user transaction (20%). The weighted score is a prioritization device, not a product rule. A score of 3.5 or higher is proposed for pilot consideration, provided no gate fails. Organizations may adjust the weights, but they should document the change before scoring to avoid outcome-driven weighting.

International Journal of Supply Chain and Logistics
ISSN 2520-3983 (Online)
Vol. 10, Issue No. 7, pp 36 - 46, 2026
www.carijournals.org




Figure 3. Two-stage selection logic: eligibility gates followed by weighted shaping criteria.

Table 3. Worked application of the framework. Cases are constructed, not customer observations.

Constructed case	Gate outcome	Weighted score	Recommendation and rationale
A. PO receipt to fixed bin; no QM/VAS; embedded EWM	Pass	4.6/5	Pilot synchronous posting. The bin is known and intermediate delivery functions are not required.
B. Vendor receipt requiring inspection lot and delivery-based quality steps	Fail	Not scored	Retain delivery-based flow. A mandatory process function depends on the delivery-centric design.
C. Mixed warehouse: standard receipts plus inspected/serialized receipts	Pass only for standard subset	4.0/5 for standard subset	Split the portfolio. Pilot synchronous posting only for the eligible subset; retain delivery-based processing elsewhere.

International Journal of Supply Chain and Logistics
ISSN 2520-3983 (Online)
Vol. 10, Issue No. 7, pp 36 - 46, 2026
www.carijournals.org

7. VALUE REALIZATION AND SENSITIVITY ANALYSIS

Value should be measured rather than presumed. Fewer system documents do not automatically translate into labor savings because document creation is largely automated. Labor value arises only if the design demonstrably reduces user steps, queue diagnosis, reprocessing, reconciliation, or support effort. The baseline should therefore capture both transaction time and exception-management time.

For illustration, annual gross labor value is calculated as: covered movements per day × seconds saved per covered movement ÷ 3,600 × loaded hourly rate × operating days. The model assumes 2,000 total movements per day, 250 operating days, and a loaded labor rate of US$28 per hour. Coverage and time saving are varied below. These are planning assumptions, not findings.

Table 4. Sensitivity analysis using 2,000 movements/day, 250 days/year, and US$28/hour. Excludes implementation and operating costs.

Eligible share of movements	Measured time saved per eligible movement	Illustrative annual gross labor value
25%	10 sec	US$9,722
25%	25 sec	US$24,306
25%	40 sec	US$38,889
50%	10 sec	US$19,444
50%	25 sec	US$48,611
50%	40 sec	US$77,778
75%	10 sec	US$29,167
75%	25 sec	US$72,917
75%	40 sec	US$116,667

Net value must deduct one-time design, configuration, regression-testing, training, and cutover costs, as well as recurring monitoring and release-validation effort. A pilot business case should also include the cost of failed postings, operational delay during EWM unavailability, and any additional capacity required at peak load. Benefits should be reported separately as observed transaction-time reduction, observed queue/support reduction, and avoided reconciliation effort.

International Journal of Supply Chain and Logistics
ISSN 2520-3983 (Online)
Vol. 10, Issue No. 7, pp 36 - 46, 2026
www.carijournals.org

8. IMPLEMENTATION, PILOT, AND CONTROLS

A controlled implementation should proceed through four stages. First, build a movement inventory by movement type, reference document, warehouse, user group, and required functions. Second, apply the gates and document the source used to confirm support. Third, execute a pilot in a non-production environment using positive, negative, reversal, partial-quantity, peak-volume, and master-data-error cases. Fourth, deploy a limited production scope with predefined monitoring and rollback criteria.

Table 5. Pilot controls and acceptance evidence. Final thresholds must be set from site baselines.

Control area	Pilot measure	Example decision rule
Posting performance	Median and 95th-percentile posting time	No material degradation versus the approved baseline
Reliability	Successful postings and error categories	All critical negative paths return understandable, recoverable errors
Operational effort	User touch time and support minutes per 1,000 movements	Observed reduction must exceed implementation run cost
Stock consistency	IM/EWM reconciliation exceptions	No unresolved discrepancy attributable to the pilot
Scope discipline	Share of movements routed outside approved scenario	Zero unauthorized use
Rollback	Documented switch-back and open-document handling	Rollback tested before production activation

9. DISCUSSION

The comparison supports a bounded conclusion. Synchronous posting is attractive when the delivery and warehouse request add little process value, the target release supports the exact scenario, and master data permit reliable determination of warehouse execution data. Delivery-based processing remains preferable when process control depends on delivery objects or when buffering and decoupling are operationally important.

The coupling perspective adds an important counterweight to document simplification. Removing a queue eliminates queue backlog for the covered interface, but it also removes that queue as a buffer. Consequently, the pilot must test EWM availability, locking, peak load, and failure recovery. This is why the framework treats synchronous availability risk as a shaping criterion and requires rollback evidence.

The proposed split-portfolio design is not a compromise of convenience. It is a deliberate architecture in which each movement follows the model that matches its functional needs. Governance is essential because later process changes, such as adding inspection, packing, serialization, or return requirements, can invalidate an earlier eligibility decision.

10. LIMITATIONS

This study is based on documentation and practitioner sources rather than a controlled multi-site implementation study. The scenarios and financial model are constructed. No site-level claim is made regarding movement mix, cycle-time improvement, or annual savings. Product scope changes by SAP S/4HANA release, and some SAP support material requires customer access. The framework therefore requires release-specific verification and local pilot evidence before production use. Future research should validate the weighting model across industries and compare posting latency, error rates, and support effort using observed data.

11. CONCLUSION AND RECOMMENDATIONS

Synchronous goods movement posting can simplify eligible embedded-EWM movements by avoiding delivery and warehouse-request objects and by returning posting errors online. Its value is conditional, not universal. The design trades broader delivery-based functionality and asynchronous buffering for a shorter synchronous path.

The practical recommendation is to use a two-stage decision. First, verify deployment, release, movement, and required functions as mandatory gates. Second, prioritize eligible candidates using documented weights for simplicity, bin determination, queue or latency burden, user fit, and runtime risk. Only then should the organization pilot the scenario and measure transaction time, exception effort, reliability, stock consistency, and peak-load behavior.

Production approval should require a completed screening checklist, traceable SAP evidence, successful negative-path and rollback tests, and a benefits model based on observed pilot data. Mixed estates should retain delivery-based processing for complex movements while using synchronous posting only for the verified, stable subset.

DECLARATIONS

Conflict of interest: The authors declare no conflict of interest.

Funding: No external funding was reported for this study.

Data availability: No empirical dataset was used. The worked scenarios and sensitivity analysis are constructed and fully described in the article.

Author disclosure: Product names and trademarks belong to their respective owners. The article reflects the authors' analysis and does not constitute an official statement by SAP SE, MYGO Consulting Inc., or ACCO Brands.

REFERENCES

[1] SAP SE. SAP Extended Warehouse Management product documentation. SAP Help Portal. Accessed October 26, 2026.

[2] SAP SE. Communication of Goods Movements from EWM to Inventory Management. SAP Help Portal, SAP S/4HANA on-premise documentation. Accessed October 26, 2026.

[3] SAP SE. Synchronous Goods Movement with the Post Goods Movement App. What's New in SAP S/4HANA 2020. 2020. Accessed October 26, 2026.

[4] Kumar, S. Synchronous Goods Receipts in EWM for External Procurement (PO Based) with MIGO. SAP Community. August 7, 2021. Accessed October 26, 2026.

[5] Rani Mothilal, K. Performing Synchronous Goods Movement Posting in Embedded EWM: A Complete Guide. SAP PRESS. 2026. Accessed October 26, 2026.

[6] Cloudbook editorial team. EWM PP Integration: Synchronous Goods Movement. November 5, 2024. Accessed October 26, 2026.

[7] Hohpe, G., and Woolf, B. Enterprise Integration Patterns: Designing, Building, and Deploying Messaging Solutions. Addison-Wesley, 2003.

[8] SAP SE. KBA 3452904: Activate Synchronous Goods Movements in the Warehouse. SAP for Me / SAP Support Portal. Accessed October 26, 2026.

2026 by the Authors. This Article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (http://creativecommons.org/licenses/by/4.0/)